

## EAGLE® Polyurethane Belting

### Eagle Red 85 Quick Connect

Size	Dimensions (mm)		Minimum Pulley Ø (mm)	Working Load @ percent Tension								Weight
	OD	ID		4%		6%		8%		10%		
				lbs	N	lbs	N	lbs	N	lbs	N	kg/m
<b>PC-6QC</b>	6	2.5	48	0.7	3.2	1.1	5	1.5	6.7	1.9	8.3	0.028
<b>PC-8QC</b>	8	3.2	64	1.3	5.8	2	9	2.7	12.1	3.4	14.9	0.051
<b>PC-10QC</b>	10	3.8	80	2.1	9.3	3.2	14.4	4.3	19.3	5.3	23.8	0.081
<b>PC-12QC</b>	12	5.2	96	2.8	12.6	4.4	19.7	5.9	26.3	7.3	32.5	0.11

\*All sizes are available for purchase / mtr

\*\*Quick Connect Joiners sold seperately



All above sizes are kept in stock at Finer Power Transmissions - other sizes and variations are available on request.

Every effort has been taken to ensure that the data listed in this catalogue is correct. Finer Power Transmissions P/L will not accept liability for any damage or loss caused as a result of the data in this catalogue.

#### WA HEAD OFFICE

Unit 1 / 45 Inspiration Drive WA 6065  
 ☎ (08) 9303 4966 📠 (08) 9303 4977  
 ✉ info@chainanddrives.com.au

#### NSW HEAD OFFICE

Unit 7 / 70 Holbeche Road Arndell Park NSW 2148  
 ☎ (02) 9674 8611 📠 (02) 9674 8363  
 ✉ salesnsw@chainanddrives.com.au

[www.chainanddrives.com.au](http://www.chainanddrives.com.au)