

Ribbed / Special Construction Belts

RIBBED BELTS

PIX-X'ceed® INDUSTRIAL POLY V-BELTS

PH	2.9	1.60	13	280 mm	5080 mm		
PJ	3.8	2.34	20	280 mm	5080 mm		
PK	4.5	3.56	50	280 mm	5080 mm		
PL	7.6	4.70	75	280 mm	5080 mm		
PM	13.3	9.40	180	280 mm	5080 mm		

PIX-X'ceed® DS DOUBLE SIDED POLY V-BELTS

DPK	2 to 13 ribs	1195 mm	3105 mm	
DPL	2 to 11 ribs	1200 mm	3105 mm	

PIX-X'ceed® EL ELASTICATED POLY V-BELT(PJ)

EL nPJ	2 to 20	600 mm	3105 mm
--------	---------	--------	---------

Note: n = no. of ribs

PIX-X'ceed® HT EPDM POLY V-BELTS

Features:

- Working Temperature up to 130°C.
- Abrasion & Flex cracking resistance is very high.
- Longer service life as compared to regular belts.
- Good dimensional stability.
- Higher power transmission.

Applications:
Automobiles, High Speed Engines.

SPECIAL CONSTRUCTION BELTS

PIX-X'set® PT-0

B (17x14)	17 mm	14 mm	3 mm	85"	658"	Li	
B (17x16)	17 mm	16 mm	5 mm	85"	658"	Li	
A (13x13)	13 mm	13 mm	5 mm	48"	257"	Li	
37 x 25	37 mm	25 mm	5 mm	4064 mm	16713 mm	Lp	

PIX-X'set® PT-HC HONEY COMB BELTS

B (17x17)	17 mm	17 mm	6 mm	32"	658"	Li
C (22x20)	22 mm	20 mm	6 mm	38"	658"	Li

PIX-X'set® PT-6

B (17x22)	17 mm	22 mm	11 mm	85"	375"	Li
B (17x26)	17 mm	26 mm	15 mm	66"	375"	Li
B (17x21)	17 mm	21 mm	10 mm	42"	79"	Li
C (22x25)	22 mm	25 mm	11 mm	73"	350"	Li

PIX-X'set® PT-7

37(37x25)	37 mm	25 mm	7 mm	4064 mm	8890 mm	Lp
D (32x26)	32 mm	26 mm	7 mm	142"	633"	Li

PIX-X'set® DS HEXAGONAL BELTS

AA	13.0 mm	10.0 mm	40	IS 11038, ISO 5289	80 mm	43" 260"	Li
BB	17.0 mm	14.0 mm	40	IS 11038, ISO 5289	125 mm	40" 660"	Li
CC	22.0 mm	17.0 mm	40	IS 11038, ISO 5289	224 mm	73" 658"	Li
25	25.0 mm	22.0 mm	40	RMA IP 21, IS 11038, ISO 5289	280 mm	89" 681"	Le

La: Outside Length Li: Inside Length Lp Pitch Length